

Circular Motion

WHAT IS CIRCULAR MOTION?

Circular motion refers to an object undergoing motion in a circular path that can be specified by a radius, r , and angular position, θ . The study of circular motion is referred to as the kinematics of circular motion.

The distance traveled by an object undergoing circular motion is defined as:

$$s = \theta r$$

The **angular velocity**, ω , of an object is defined as the derivative of the angular position with respect to time:

$$\omega = \frac{d\theta}{dt}$$

The **angle acceleration**, α , is defined as the derivative of the angular velocity with respect to time:

$$\alpha = \frac{d\omega}{dt}$$

LINEAR AND CIRCULAR MOTION RELATIONSHIPS

Linear motions and circular motions are connected, and they can be converted from one to another. The linear velocity, v , of the object is always tangential to the circular direction and has a magnitude of:

$$v = \omega r$$

The linear acceleration of the object is decomposed into radial and tangential acceleration. The radial acceleration is defined as:

$$a_r = \frac{v^2}{r} = \omega^2 r$$

and is pointing towards the center of the circle. While the tangential acceleration is defined as:

$$a_t = \alpha r$$

and acts perpendicular to the radial direction. The total acceleration is defined as:

$$a = \sqrt{a_r^2 + a_t^2}$$

CONSTANT ANGULAR ACCELERATION

If the object's motion is described with constant angular acceleration, the following equations are valid and can be used:

$$\begin{aligned}\theta_f &= \theta_i + \omega_i \Delta t + \frac{1}{2} \alpha \Delta t^2 \\ \omega_f &= \omega_i + \alpha \Delta t \\ \omega_f^2 &= \omega_i^2 + 2 \alpha \Delta \theta\end{aligned}$$

SAMPLE PROBLEMS

1. A 900-kg car moving at 10 m/s drives around a circle with a radius of 25.0 m. Determine the acceleration and the net force acting upon the car. [4 m/s², 3600N]
2. A 95-kg halfback makes a turn on the football field. The halfback sweeps out a path that is a portion of a circle with a radius of 12-meters. The halfback makes a quarter of a turn around the circle in 2.1 seconds. Determine the speed, acceleration and net force acting upon the halfback. [9 m/s, 6.7 m/s², 637 N]
3. The Wall of Death is a circus act in which cars and motorcycles drive along the inside of a vertical cylinder/silo as shown in the figure below. The cars are capable of travelling at a maximum of 30.0 m/s while in the cylinder. Coefficients of friction between rubber and concrete are given as $\mu_s = 1.00$ and $\mu_k = 0.800$. What is the maximum diameter of the cylinder/silo so that cars can safely travel around the cylinder without drivers falling to their deaths? At this speed, how long does it take a car to travel ten revolutions within the cylinder? [184 m; 192 s]

